TECHNICAL DATA SHEET



EMULSIL® 35

SILICONE EMULSION

EMULSIL® 35 is an emulsion in water of Polidimethvilsiloxane (Silicone Oil).

Characteristics

Appearance: Milky white water emulsion based on Silicone Oil (Fluid MS) medium viscosity

Odour: None (VOC=zero VOC Free)

Solid Content: 35% Silicone Content: 32%

Density: 1,02 g/cm3

Viscosity: 50-100 mPas (25°C)

pH: 6/7 (stable in pH range 3-12) Emulsifiers: Non ionic (biodegradable >80%)

(APEO Free)

Solubility: Emulsion in all ratios in water

Applications

EMULSIL® 35 is a silicone emulsion used in the following processes:

RUBBER: Releasing agent for mould in rubber materials forming: vulcanization of tyres, extrusion of pipes and technical articles (or bellows).

DETERGENT: Antistatic and sliding in the formulation of products for house, cars, detergents and polishers PAPER: Lubricating antistatic and sliding for the print of magazines in the offset printing. It is used to eliminate electrostatic current that may appear during printing and it improves the shining of the paper.

THREADS: Lubricating for yarns and cotton, antistatic.

FOUNDRY: Releasing agent for moulds in shell moulding fusion

TEXTILE AND LEATHER: Sliding, antistatic and Softener agenct added into the formulation of leather and textile chemicals, to improve the soft hand and silicone hand

Instructions of use

EMULSIL® 35 can be used as supplied or diluted to water for 60 times in conformity with use or experience. It is used with a brush, with sprinkle or for immersion. Shake well before using it or diluting it especially after being stored up for a long time.

Storage

EMULSIL® 35 must be keeping from freezing. Store in an original unopened container at temperature from +5°C to 35°C away from direct sunlight the product is stable at least 12 month from Production Manufacture Date.

Packaging

Pots of kg 1 – 15 pcs boxes Product Code 20250/01 25-50-120-200 kg drums and 1000 kg IBC Plastic Tanks Product Code 20250/50

Revision date 29.04.2020

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

Tel: +39 0444 649766 Fax: +39 0444 440018

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

SILICONI COMMERCIALE® Technical data- sheet



email: info@siliconi.it

www.siliconi.it

